

# EMS-D 10250

## Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi / Pump Type	Motor Tipi / Motor Type	Güç / Power	Güç / Power	m <sup>3</sup> /h	0	155	196	234	262	295	Outlet (Inch)	Pump Dia.	Max. Pump Dia.	Pompa Uzunluğu / Pump Length	Pompa Ağırlığı / Pump Weight
		HP	kW		0	43	54,5	65	73	82		mm		mm	LA (mm)
10250 / 01	6" - 8" - 10"	30	22	MMS (m)	47	36	31	26	31	14	6"	245	260	650	55
10250 / 02		60	45		93	71	61	52	42	27				840	77
10250 / 03		90	66		140	107	92	78	63	41				1030	99
10250 / 04		125	92		187	142	122	104	83	55				1220	121
10250 / 05		150	110		233	178	152	129	104	69				1410	143

### ÜRÜN ÖZELLİKLERİ

Difüzör	Pik Döküm	GG20
Fan **	Pik Döküm	GG20
Çıkış Gövdesi	Pik Döküm	GG20
Emme Kutusu	Pik Döküm	GG20
Pompa Mili	Paslanmaz Çelik	AISI 420
Kaplin	Paslanmaz Çelik	AISI 420
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Klepe	Paslanmaz Çelik	AISI 304
** Bronz Fan Opsiyoneldir.		

### PRODUCT SPECIFICATIONS

Diffuser	Cast Iron	GG20
Impeller **	Cast Iron	GG20
Outlet Body	Cast Iron	GG20
Suction Case	Cast Iron	GG20
Pump Shaft	Stainless Steel	AISI 420
Coupling	Stainless Steel	AISI 420
Filter & Cable Guard	Stainless Steel	AISI 304
Valve Cap	Stainless Steel	AISI 304
** Bronze Impeller is Optional.		