

EMS-D 6050

Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU/ PERFORMANCE CHART

Pompa Tipi/ Pump Type	Motor Tipi/ Motor Type	Güç/ Power	Güç/ Power	m ³ /h	0	26	41	46	50	55	60	66	68	Outlet (Inch)	Pump Dia.	Max. Pump Dia.	Pompa Uzunluğu/ Pump Length	Pompa Ağırlığı/ Pump Weight
		HP	kW		0	7,2	11	13	14	15	17	18	19					
					lt/s													
6050 / 03	6"	7,5	5,5	MMS (m)	46	40	34	31	28	25	19	12	9	3" 4"	146	161	755	35
6050 / 04		10	7,5		62	54	45	41	37	33	25	16	12				885	47
6050 / 05		15	11		77	67	57	52	46	41	31	21	15				1015	58
6050 / 06		15	11		83	80	68	62	56	49	37	25	19				1145	70
6050 / 07		20	15		108	94	79	72	65	58	43	29	22				1275	82
6050 / 08		20	15		124	107	91	82	74	66	49	33	25				1405	93
6050 / 09		25	18,5		139	121	102	93	83	74	56	37	28				1535	105
6050 / 10		30	22		155	134	113	103	93	82	62	41	31				1665	117
6050 / 11		30	22		170	147	125	113	102	91	68	45	34				1795	128
6050 / 12		40	30		185	161	136	124	111	99	74	49	37				1925	140
6050 / 13		40	30		201	174	147	134	121	107	80	54	40				2055	152
6050 / 14		50	37		216	187	159	144	130	115	87	58	43				2185	163
6050 / 15		50	37		232	201	170	155	139	124	93	62	46				2315	175

ÜRÜN ÖZELLİKLERİ

Difüzör	Pik Döküm	GG20
Fan **	Pik Döküm	GG20
Çıkış Gövdesi	Pik Döküm	GG20
Emme Kutusu	Pik Döküm	GG20
Pompa Mili	Paslanmaz Çelik	AISI 420
Kaplin	Paslanmaz Çelik	AISI 420
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Klepe	Paslanmaz Çelik	AISI 304
** Bronz Fan Opsiyoneldir.		

PRODUCT SPECIFICATIONS

Diffuser	Cast Iron	GG20
Impeller **	Cast Iron	GG20
Outlet Body	Cast Iron	GG20
Suction Case	Cast Iron	GG20
Pump Shaft	Stainless Steel	AISI 420
Coupling	Stainless Steel	AISI 420
Filter & Cable Guard	Stainless Steel	AISI 304
Valve Cap	Stainless Steel	AISI 304
** Bronze Impeller is Optional.		