

EMS-D 7075

Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi/ Pump Type	Motor Tipi/ Motor Type	Güç/ Power	Güç/ Power	m ³ /h lt/s	0	51	60	66	75	87	99	110	Outlet (Inch)	Pump Dia.	Max. Pump Dia.	Pompa Uzunluğu/ Pump Length	Pompa Ağırlığı/ Pump Weight
		HP	kW		0	14,2	16,6	18,3	20,8	24,1	27,5	30,6		mm	mm	LA (mm)	Kg
		6" 7" 8"	MMS (m)		4" 5"	175	190										
7075 / 01		7,5	5,5		24	20	19	18	17	15	14	12				520	28
7075 / 02		15	11		44	40	39	38	36	33	28	23				645	36
7075 / 03		20	15		65	57	55	54	51	46	40	30				770	46
7075 / 04		25	18,5		81	74	70	67	62	56	48	36				895	55
7075 / 05		30	22		105	85	80	76	70	63	54	41				1020	63
7075 / 06		40	30		122	103	98	93	84	74	61	46				1145	71
7075 / 07		50	37		142	123	118	112	103	85	72	55				1270	79
7075 / 08		60	45		164	143	137	132	123	112	94	75				1395	87
7075 / 09		70	51		190	167	161	156	147	134	115	89				1520	95
7075 / 10		80	59		216	188	182	177	168	152	130	100				1645	103
7075 / 11		90	66		237	210	202	197	184	166	145	114				1770	112
7075 / 12		90	66		258	230	222	216	204	187	163	121				1895	120
7075 / 13		100	75		282	252	242	235	221	202	177	138				2020	129

ÜRÜN ÖZELLİKLERİ

Difüzör	Pik Döküm	GG20
Fan **	Pik Döküm	GG20
Çıkış Gövdesi	Pik Döküm	GG20
Emme Kutusu	Pik Döküm	GG20
Pompa Mili	Paslanmaz Çelik	AISI 420
Kaplin	Paslanmaz Çelik	AISI 420
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Klepe	Paslanmaz Çelik	AISI 304
** Bronz Fan Opsiyoneldir.		

PRODUCT SPECIFICATIONS

Diffuser	Cast Iron	GG20
Impeller **	Cast Iron	GG20
Outlet Body	Cast Iron	GG20
Suction Case	Cast Iron	GG20
Pump Shaft	Stainless Steel	AISI 420
Coupling	Stainless Steel	AISI 420
Filter & Cable Guard	Stainless Steel	AISI 304
Valve Cap	Stainless Steel	AISI 304
** Bronze Impeller is Optional.		