

# EMS-D 8120

## Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi/ Pump Type	Motor Tipi/ Motor Type	Güç/ Power	Güç/ Power	m <sup>3</sup> /h	0	18	36	54	72	90	115	120	126	144	Outlet (Inch)	Pump Dia.	Max. Pump Dia.	Pompa Uzunluğu/ Pump Length	Pompa Ağırlığı/ Pump Weight
		HP	kW		lit/s	0	5	10	15	20	25	33	33,3	35		40	mm	mm	LA (mm)
8120 / 01	6" 8"	10	7,5	MMS (m)	28	25	23	21	20	17	15	13	12	10	5" 6"	190	205	560	34
8120 / 02		20	15		56	50	46	42	40	34	30	26	24	17				720	47
8120 / 03		30	22		84	75	71	63	60	51	45	40	36	32				880	56
8120 / 04		40	30		112	100	96	84	80	68	60	58	54	47				1040	66
8120 / 05		50	37		140	131	125	122	115	95	77	71	68	54				1200	77
8120 / 06		60	45		168	152	141	130	125	109	92	88	81	65				1360	88
8120 / 07		70	51		196	178	165	152	146	127	108	100	95	76				1520	96
8120 / 08		80	59		224	203	189	174	167	145	123	115	109	87				1680	110
8120 / 09		90	66		252	229	217	196	188	163	139	130	122	98				1840	121
8120 / 10		100	75		280	254	236	218	209	181	154	148	136	109				2000	132
8120 / 11		110	81		308	280	260	240	230	200	170	160	150	120				2160	143

### ÜRÜN ÖZELLİKLERİ

Difüzör	Pik Döküm	GG20
Fan **	Pik Döküm	GG20
Çıkış Gövdesi	Pik Döküm	GG20
Emme Kutusu	Pik Döküm	GG20
Pompa Mili	Paslanmaz Çelik	AISI 420
Kaplin	Paslanmaz Çelik	AISI 420
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Klepe	Paslanmaz Çelik	AISI 304
** Bronz Fan Opsiyoneldir.		

### PRODUCT SPECIFICATIONS

Diffuser	Cast Iron	GG20
Impeller **	Cast Iron	GG20
Outlet Body	Cast Iron	GG20
Suction Case	Cast Iron	GG20
Pump Shaft	Stainless Steel	AISI 420
Coupling	Stainless Steel	AISI 420
Filter & Cable Guard	Stainless Steel	AISI 304
Valve Cap	Stainless Steel	AISI 304
** Bronze Impeller is Optional.		