

EMS-D 8145

Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi/ Pump Type	Motor Tipi/ Motor Type	Güç/ Power	Güç/ Power	m ³ /h	0	28	61	72	94	122	130	145	162	180	Outlet (Inch)	Pump Dia.	Max. Pump Dia.	Pompa Uzunluğu/ Pump Length	Pompa Ağırlığı/ Pump Weight
		HP	kW		0	8	17	20	26	34	36	40,2	45	50		mm	mm	LA (mm)	Kg
8145 / 01	6" 8"	15	11	MMS (m)	30	26	23	22	20	17	16	13	10	7	5" 6"	190	205	560	34
8145 / 02		25	18,5		60	52	46	44	40	35	32	26	20	14				720	45
8145 / 03		40	30		90	78	70	67	61	52	49	39	33	21				880	56
8145 / 04		50	37		120	106	93	89	81	69	65	53	44	28				1040	67
8145 / 05		60	45		150	132	117	112	102	86	81	66	56	35				1200	77
8145 / 06		70	51		180	159	140	134	122	104	98	79	67	42				1360	88
8145 / 07		80	59		210	185	164	157	142	121	114	92	78	49				1520	99
8145 / 08		90	66		240	212	187	179	163	138	130	106	89	56				1680	110
8145 / 09		100	75		270	238	211	202	183	156	147	119	101	64				1840	121
8145 / 10		110	81		300	265	234	204	204	173	100	132	112	71				2000	132

ÜRÜN ÖZELLİKLERİ

Difüzör	Pik Döküm	GG20
Fan **	Pik Döküm	GG20
Çıkış Gövdesi	Pik Döküm	GG20
Emme Kutusu	Pik Döküm	GG20
Pompa Mili	Paslanmaz Çelik	AISI 420
Kaplin	Paslanmaz Çelik	AISI 420
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Klepe	Paslanmaz Çelik	AISI 304
** Bronz Fan Opsiyoneldir.		

PRODUCT SPECIFICATIONS

Diffuser	Cast Iron	GG20
Impeller **	Cast Iron	GG20
Outlet Body	Cast Iron	GG20
Suction Case	Cast Iron	GG20
Pump Shaft	Stainless Steel	AISI 420
Coupling	Stainless Steel	AISI 420
Filter & Cable Guard	Stainless Steel	AISI 304
Valve Cap	Stainless Steel	AISI 304
** Bronze Impeller is Optional.		