

# EMS-N 403

## Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi / Pump Type	Güç / Power	Güç / Power	m <sup>3</sup> /h	0	1,8	2,4	3	3,6	4,2	4,8	5,4	Outlet (Inch)	Pump Dia.	Max. Pump Dia.	Pompa Uzunluğu / Pump Length	Pompa Ağırlığı / Pump Weight
	HP	kW		0	0,5	0,66	0,83	1	1,16	1,33	1,5		mm	mm	LA (mm)	Kg
403-07	0,75	0,55	MMS (m)	54	48	44	41	35	29	21	13	1 1/4"	94	98	425	4,7
403-09	1	0,75		66	59	54	49	39	32	23	14				513	5,3
403-10	1	0,75		74	66	60	55	44	36	26	15				541	5,5
403-14	1,5	1,1		104	95	88	79	68	54	37	22				691	6,3
403-18	2	1,5		132	116	107	93	80	60	43	24				808	7,3
403-27	3	2,2		198	179	165	150	124	96	65	27				1090	9,3
403-35	4	3		245	221	200	192	160	124	77	38				1355	10,9
403-44	5,5	4		308	278	252	218	190	145	97	48				1630	13
403-48	5,5	4		336	303	274	237	207	158	105	52				1750	13,5

### ÜRÜN ÖZELLİKLERİ

Pompa Gövdesi	Paslanmaz Çelik	AISI 304
Pompa Mili	Paslanmaz Çelik	AISI 420
Difüzör	Plastik	Norly (PPO)
Difüzör Çanağı	Paslanmaz Çelik	AISI 304
Fan	Plastik	Norly (PPO)
Kaplin	Paslanmaz Çelik	AISI 304
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Yatak Takımı	Kauçuk	NBR
Çanak Yatağı	Plastik	Poliüretan
Klepe	Paslanmaz Çelik	AISI 304
Emiş Gövdesi	Paslanmaz Çelik	AISI 304
Çıkış Gövdesi	Paslanmaz Çelik	AISI 304

### PRODUCT SPECIFICATIONS

Pump Body	Stainless Steel	AISI 304
Pump Shaft	Stainless Steel	AISI 420
Diffuser	Plastic	Norly (PPO)
Diffuser Ring	Stainless Steel	AISI 304
Impeller	Plastic	Norly (PPO)
Coupling	Stainless Steel	AISI 304
Filter & Cable Guard	Stainless Steel	AISI 304
Bearing Set	Rubber	NBR
Diffuser Bearing	Plastic	Poliüretan
Valve Cap	Stainless Steel	AISI 304
Suction Body	Stainless Steel	AISI 304
Delivery Body	Stainless Steel	AISI 304