

# EMS-P 403

## Pompa Teknik Özellikleri / Pump Technical Specifications



Dalgıç Motor ve Pompa / Submersible Motor and Pump

PERFORMANS TABLOSU / PERFORMANCE CHART

Pompa Tipi / Pump Type	Güç / Power	Güç / Power	m <sup>3</sup> /h	0	1,5	1,8	2,1	2,4	2,7	3	3,6	4,2	Outlet (Inch)	Pump Dia. mm	Max. Pump Dia. mm	Pompa Uzunluğu / Pump Length LA (mm)	Pompa Ağırlığı / Pump Weight Kg
	HP	kW		00	0,42	0,50	0,58	0,67	0,75	0,83	10	1,17					
403-09	0,75	0,55	MMS (m)	57	49	47	46	44	41	38	30	19	1 1/4"	94	98	356	3
403-12	1	0,75		77	66	64	62	58	56	52	43	28				419	3,6
403-15	1,5	1,1		97	85	83	80	77	74	69	57	40				482	4,2
403-18	1,5	1,1		116	101	97	94	90	85	80	67	45				545	4,7
403-22	2	1,5		143	127	120	115	110	105	97	80	54				629	5,5
403-25	2	1,5		160	139	134	128	124	117	110	90	60				692	6,1
403-29	3	2,2		185	160	155	149	143	136	127	103	70				776	6,8
403-33	3	2,2		211	183	177	172	164	155	145	118	80				883	9,7
403-39	4	3		252	219	213	204	195	185	172	138	94				1009	11,2
403-45	4	3		288	250	243	233	224	213	199	162	110				1135	12,7
403-52	5,5	4		334	291	282	272	261	247	230	184	123				1282	14,5

### ÜRÜN ÖZELLİKLERİ

Difüzör	Paslanmaz Çelik	AISI 304
Fan	Paslanmaz Çelik	AISI 304
Çıkış Gövdesi	Paslanmaz Çelik	AISI 304
Emiş Gövdesi	Paslanmaz Çelik	AISI 304
Ara Çanak	Paslanmaz Çelik	AISI 304
Kaplin	Paslanmaz Çelik	AISI 420
Fan Tespit Burcu	Paslanmaz Çelik	AISI 304
Filtre & Kablo Kanalı	Paslanmaz Çelik	AISI 304
Klepe	Paslanmaz Çelik	AISI 304
Aşınma Halkası	Paslanmaz Çelik	AISI 304
Pompa Mili	Paslanmaz Çelik	AISI 420

### PRODUCT SPECIFICATIONS

Diffuser	Stainless Steel	AISI 304
Impeller	Stainless Steel	AISI 304
Outlet Body	Stainless Steel	AISI 304
Suction Case	Stainless Steel	AISI 304
Intermediate Bowl	Stainless Steel	AISI 304
Coupling	Stainless Steel	AISI 420
Impeller Lock Collet	Stainless Steel	AISI 304
Filter & Cable Guard	Stainless Steel	AISI 304
Valve Cap	Stainless Steel	AISI 304
Wear Ring	Stainless Steel	AISI 304
Pump Shaft	Stainless Steel	AISI 420